

MAI<sup>®</sup>**4ONE**SIRIUS PLUS



MAN ASSISTING INNOVATIONS



## THE COMPACT POWERHOUSE

# MAI®4ONESIRIUS PLUS

### DISASSEMBLED IN SECONDS

The MAI®4ONE SIRIUS PLUS mortar mixing pump disassembled in seconds with just two motions and without tools, allowing it to be transported quickly from floor to floor. The small mixing pump impresses with its high power and integrated theft protection: The MAI®4ONE SIRIUS PLUS electrical box can be easily removed and locked up after the work is finished.

### LOW OPERATING COSTS, LONG SERVICE LIFE

Capable of operating on one- or three-phase current, the MAI®4ONE SIRIUS PLUS is suitable for processing both dry mortars and pre-mixed wet products. The variable pumping capacity helps to precisely meet your needs in particular when pumping wet products. The rapid decomposability as well as the optionally available worm pump quick switch-over device makes the MAI®4ONE SIRIUS PLUS a pleasure to work with. And the innovative MAI®EASY-CLEAN plastic mixing zone also happens to help you save money on wearing parts and operating costs.

### ONE FOR ALL

The mortar mixing pump MAI®4ONE SIRIUS PLUS can be reliably used to process practically any pumpable dry mortar, paste - like compounds and adhesive mortars. It is also recommended for manually processing bagged dry materials as well as fully automatic delivery from a silo.

The typical areas of application include:

Interior and exterior lime, lime-cement-based plasters, renovation plaster, scraped render, frame mortar, levelling compounds, the application of adhesive in composite thermal insulation systems and the embedding of textiles in particular.

### THE ADVANTAGES AT A GLANCE

- Disassembled in seconds - and offers theft protection with the removable electrical box
  - One- or three-phase current operation - suitable for practically any power socket
- Low operating costs thanks to MAI®SPEED-CLEANING and reduced wear
  - MAI®EASY-CLEAN system: the new self-cleaning mixing tube from MAI®
  - Optional worm pump quick switch-over device saves additional time

### TECHNICAL DATA

Operating voltage:	400V/3/PE/N/50Hz or 230V/1/PE/50Hz
Nominal power:	6,8 or 3,3 kW
Surge protection:	16 or 25 A
Delivery rate:	7 - 35 l/min or 2 - 20 l/min
L x W x H:	150 x 60 x 120 cm
Filling height:	104 cm

### WEIGHTS

Control unit:	45 kg
Mixer:	49 kg
Drive unit:	45 kg
Compressor:	22 kg
Total weight:	161 kg



Dulux AcraTex  
1 Jeanes St Beverley SA 5009

**Dulux Customer Service 13 23 77**  
**[www.acratex.com.au](http://www.acratex.com.au)**